## **EUROPEAN PATENT OFFICE**

## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

03274479

**PUBLICATION DATE** 

05-12-91

APPLICATION DATE

26-03-90

**APPLICATION NUMBER** 

02077440

APPLICANT: YUASA CORP;

INVENTOR:

YAMANAKA MASAO;


INT.CL.

G01R 31/36

TITLE

METHOD OF DETERMINING LIFETIME

OF LEAD STORAGE BATTERY



ABSTRACT: PURPOSE: To enable accurate judgement of the lifetime of a lead storage battery employed in a floating charged state by measuring an internal impedance of the lead storage battery by subtracting a measured current of an internal impedance measurer from a ripple current contained in a charging current and by dividing a measured voltage of the internal impedance measurer by a difference current.

> CONSTITUTION: A ripple current contained in a charging current of a lead storage battery 3 connected in a floating charged state through a rectifier 2 is subtracted from a measured current of an internal impedance measurer 6. In other words, an AC ammeter is inserted into a charging circuit of the lead storage battery 3 and a measured value of this AC ammeter 5 and a measured value of an AC ammeter 6-2 of the internal impedance measurer 6 are inputted to a subtractor 7, so as to calculate a difference current. Then, the measured voltage of the internal impedance measurer 6 is divided by this difference current and a value thus obtained is indicated as an internal impedance. By this constitution, the internal impedance in the floating charged state can be measured accurately.

COPYRIGHT: (C) JPO